

24"x48" Porcelain Field Tile - Matte Soft Textured



Ice
100008723



Light
100008724



Classic
100008725

36"x36" Porcelain Field Tile - Matte Soft Textured



Ice
100008726



Light
100008727



Classic
100008728

24"x48" Coast Deco Ceramic Tile - Matte Soft Textured



Ice
100008729



Light
100008730



Classic
100008731

4"x4" Offset Porcelain Mosaic - Matte Soft Textured (11"x13" Sheet)



Ice
100009013



Light
100009014



Classic
100009015

Oda

Glazed Color Body Porcelain and Glazed Ceramic


Photo Features Oda 24"x48" Porcelain Tile & 4"x4" Offset Porcelain Mosaic - Matte Soft Textured in Ice

SIZING & PACKAGING

Type	Shape	Ice Code	Light Code	Classic Code	Size	Description	Pcs / Ctn	Sf / Ctn
Field		100008723	100008724	100008725	24"x48"	Porcelain Tile - Matte Soft Textured	2	15.39
		100008726	100008727	100008728	36"x36"	Porcelain Tile - Matte Soft Textured	2	15.39
Deco		100008729	100008730	100008731	24"x48"	Coast Deco Ceramic Tile - Matte Soft Textured	2	17.33
Mosaic		100009013	100009014	100009015	11"x13" Sheet	4"x4" Offset Porcelain Mosaic - Matte Soft Textured	10	-


ANSI TECHNICAL SPECIFICATIONS

	DCOF Acutest	PEI Rating ASTM# C1027	Frost Resistant ASTM# C1026	Scratch Resistance MOHS	Breaking Strength ASTM# C648	Water Absorption ASTM# C373	Chemical Resistance ASTM# C650
Results	≥0.42	3	Unaffected	N/A	≥562 lbf	≤0.5%	Unaffected




APPLICATIONS - PORCELAIN FIELD TILE

	Floors	Walls	Countertops	Shower Floors	Shower Walls	Pools/Spas
Residential	●	◻	●	●	●	●
Commercial	●	●	●	●	●	●



APPLICATIONS - PORCELAIN MOSAIC

	Floors	Walls	Countertops	Shower Floors	Shower Walls	Pools/Spas
Residential	●	◻	●	●	●	
Commercial	●	●	●	●	●	



Use of a leveling system during installation is strongly recommended

APPLICATIONS - CERAMIC 24"x48" DECO

	Floors	Walls	Countertops	Shower Floors	Shower Walls	Pools/Spas
Residential		●			●	
Commercial		●			●	



Made in Spain



Glazed-Color Body Porcelain

LEGEND

- ◻ Product rated for Interior & Exterior use
- Product rated for Interior use only
- † May be suitable for Exterior Floors
- ∅ Applications & ANSI Technical Specifications do not apply
- * Special Order only



Rectified Edge



Glazed Ceramic

IMPORTANT: Installation Instructions - We recommend wet cutting or the score and snap method during the installation process. Improper installation techniques could expose installer to inhalation of harmful silica dust. Do not dry cut product using power tools during the installation process. Using dry cutting methods could present a risk of acute lung injury. If adequate ventilation cannot be achieved, wear a mask or respirator. For more information, see the SDS at www.bedrosians.com/en/installation-care-maintenance/.

Merchandising materials and samples are for general reference only and representative of a product's potential characteristics. Tile is subject to variation in color/shade, size, texture, and finish. Field, mosaic and trim tile may not match exactly. Blend tiles from different boxes to achieve consistent shade distribution. Installer and end user must conduct a dry mock layout under proper lighting conditions to inspect the product. Installation constitutes product acceptance. Improper installation, application, use, care and maintenance voids warranty. Reference the TCNA Handbook and ANSI for installation guidance. Please visit bedrosians.com for current product information. We reserve the right to make product changes at any time without notice.

