



Crema Marfil
100005416 - 24"x48" Rectified Field Tile - Polished
100005415 - 24"x48" Rectified Field Tile - Satin



Crema Marfil
100005418 - 48"x48" Rectified Field Tile - Polished
100005417 - 48"x48" Rectified Field Tile - Satin



Crema Marfil
100005982
4"x4" Mosaic - Satin
(12"x12" Sheet)












Crema Marfil

Glazed Color Body Porcelain


Photo Features 24"x48" Rectified Field Tile - Satin in Crema Marfil.

SIZING & PACKAGING

Type		Shape	Item Code	Size	Description	Pcs / Ctn	Sf / Ctn
Field	Ø		100005416	24"x48"	Rectified Field Tile - Polished	2	15.50
			100005415	24"x48"	Rectified Field Tile - Satin	2	15.50
	Ø		100005418	48"x48"	Rectified Field Tile - Polished	2	31.00
			100005417	48"x48"	Rectified Field Tile - Satin	2	31.00
Trim	Ø		100005985	3"x24"	Bullnose - Polished	10	-
			100005984	3"x24"	Bullnose - Satin	10	-
Mosaic	Ø		100005982	12"x12" Sheet	4"x4" Mosaic - Satin	5	-


ANSI TECHNICAL SPECIFICATIONS

	DCOF Acutest	PEI Rating ASTM# C1027	Frost Resistant ASTM# C1026	Scratch Resistance MOHS	Breaking Strength ASTM# C648	Water Absorption ASTM# C373	Chemical Resistance ASTM# C650
Results	≥ 0.42	5	Unaffected	8	Pass (1,300 ISO)	≤ 0.5%	Unaffected



APPLICATIONS

	Floors	Walls	Countertops	Shower Floors	Shower Walls	Pools/Spas
Residential	●	◐	◐	●	◐	◐
Commercial	●	◐	◐		◐	◐



LEGEND

- ◐ Product rated for Interior & Exterior use
- Product rated for Interior use only
- † May be suitable for Exterior Floors
- Ø Applications & ANSI Technical Specifications do not apply
- * Special Order only



IMPORTANT: Installation Instructions - We recommend wet cutting or the score and snap method during the installation process. Improper installation techniques could expose installer to inhalation of harmful silica dust. Do not dry cut product using power tools during the installation process. Using dry cutting methods could present a risk of acute lung injury. If adequate ventilation cannot be achieved, wear a mask or respirator. For more information, see the SDS at www.bedrosians.com/en/installation-care-maintenance/.

Tiles with a polished finish are not appropriate for wet or exterior floor applications. Do not use acidic cleaners.

Merchandising materials and samples are for general reference only and representative of a product's potential characteristics. Tile is subject to variation in color/shade, size, texture, and finish. Field, mosaic and trim tile may not match exactly. Blend tiles from different boxes to achieve consistent shade distribution. Installer and end user must conduct a dry mock layout under proper lighting conditions to inspect the product. Installation constitutes acceptance of the product. Reference the TCNA, ANSI, Manufacturer's specifications, and Bedrosians Care & Maintenance Guide. Improper installation, application, use, care and maintenance voids warranty. We reserve the right to make product changes without notice. Please visit bedrosians.com for current product information.

