Shorewood

Luxury Vinyl (Stone Polymer Composite)



VyLuxe[®]

Fog 100007865 9"x60" Stone Polymer Composite Vinyl



Crema 100006807 9"x60" Stone Polymer Composite Vinyl



Sand 100006809 9"x60" Stone Polymer Composite Vinyl



Khaki 100006810 9"x60" Stone Polymer Composite Vinyl



Linen 100006811 9"x60" Stone Polymer Composite Vinyl



Canvas 100006812 9"x60" Stone Polymer Composite Vinyl



Honey 100006814 9"x60" Stone Polymer Composite Vinyl



Oak 100006813 9"x60" Stone Polymer Composite Vinyl



Driftwood 100006815 9"x60" Stone Polymer Composite Vinyl




SIZING & PACKAGING

Type	Shape	Item Code	Size	Description	Pcs/Ctn	Sf / Ctn
Plank		100000•••	9"x60"	Stone Polymer Composite - 20 Mil Wear Layer with UV Cured Polyurethane & Ceramic Bead Finishes	_	_
Trim		100000•••	94.5"x2.73"x0.98"	Luxury Vinyl Flush Stair Nose	-	-
		100000***	94.5"x1.77"x0.33"	Luxury Vinyl Reducer	-	-
	/7	100000•••	94.5"x1.77"x0.28"	Luxury Vinyl T-Mold	-	-


TECHNICAL SPECIFICATIONS

TECHNICAL SPECIFICA	*****	
Standard	Description	Result
ASTMF-387	Total Thickness	6.0 mm
ASTMF-410	Wear Layer Thickness	0.5 mm (20 mil)
ASTME-648	Critical Radiant Flux	ClassI
ASTMF-925	Chemical Resistance	No Change in 24 Hours
ASTMF-970	Static Load Limit	2,000 p.s.i.
ASTM F-1514	Resistance to Heat	Pass
ASTM F-1515	Light Resistance	Pass
ASTM F-1914	Residual Indentation	< 0.003"
ISO 23999	Dimensional Stability	Pass
ASTMF-2421	Width	±0.04mm
ASTMF-2421	Length	±1mm
ASTMF-2055	Squareness	<0.25mm
ASTM D-2047	SlipResistance	Exceeds 0.52 Dry
ISO 23999	Cupping/Curling	≤ 0.1 mm
ASTME-492	Impact Sound Transmission (IIC)	IIC64
ASTME-90	Airborne Sound Transmission (STC)	STC 61
ASTME-2179	Impact Sound Transmission (Δ IIC)	ΔIIC 24
Performance	Scratch/Scuff Resistance	Excellent
FloorScore Certified	California 01350	Pass
Warranty	Residential	10 Years
Warranty	Commercial	5 Years


LAYING PATTERNS



30% Offset



50% Offset



Random

APPLICATIONS

	Floors	Walls	Countertops	Shower Floors	Shower Walls	Pools/Spas
Residential	•					
Commercial	•					



LEGEND

Product rated for Interior & Exterior use

Product rated for Interior use only

† May be suitable for Exterior Floors

* Special Order only

Merchandising materials and samples are for general reference only and representative of a product's potential characteristics. Product is subject to variation in color/shade, size, texture, and finish. Blend product from different boxes to achieve consistent shade distribution. Installer and end user must conduct a dry mock layout under proper lighting conditions to inspect the product. Installation constitutes product acceptance. Improper installation, application, use, care and maintenance voids warranty. Reference the packaging for installation guidance. We reserve the right to make product changes at any time without notice.

