

# 8"x48" Wood Look Porcelain Tile - Matte







Roble 100007796



Brandy 100007797



Siena 100007798

# 24"x48" Wood Look Porcelain 3D Deco - Matte



Haya 100007799



Roble 100007800



Brandy 100007801



Siena 100007802



### SIZING & PACKAGING

Type	Shape	Brandy Code	Haya Code	Roble Code	Siena Code	Size	Description	Pcs/Ctn	Sf / Ctn
Field		100007797	100007795	100007796	100007798	8"x48"	Wood Look Porcelain Tile - Matte	6	15.49
Deco		100007801	100007799	100007800	100007802	24"x48"	Ribbed Wood Look Porcelain 3D Deco - Matte	2	15.49

### ANSITECHNICAL SPECIFICATIONS

	DCOF Acutest	PEI Rating ASTM# C1027	Frost Resistant ASTM# C1026	Scratch Resistance MOHS	Breaking Strength ASTM# C648	Water Absorption ASTM# C373	Chemical Resistance ASTM# C650
Results	≥0.42	4	Unaffected	5	N/A	N/A	Unaffected



## APPLICATIONS

	Floors	Walls	Countertops	Shower Floors	Shower Walls	Pools/Spas
Residential	•	•		•	•	•
Commercial	•	•		•	•	•



Use of a leveling system during installation is strongly recommended

### LEGEND

Product rated for Interior & Exterior use

Applications & ANSI Technical Specifications do not apply

Product rated for Interior use only

\* Special Order only

† May be suitable for Exterior Floors







IMPORTANT: Installation Instructions - We recommend wet cutting or the score and snap method during the installation process. Improper installation techniques could expose installer to inhalation of harmful silica dust. Do not dry cut product using power tools during the installation process. Using dry cutting methods could present a risk of acute lung injury. If adequate ventilation cannot be achieved, wear a mask or respirator. For more information, see the SDS at www.bedrosians.com/en/installation-care-maintenance/.

Merchandising materials and samples are for general reference only and representative of a product's potential characteristics. Tile is subject to variation in color/shade, size, texture, and finish. Field, mosaic and trim tile may not match exactly. Blend tiles from different boxes to achieve consistent shade distribution. Installer and end user must conduct a dry mock layout under proper lighting conditions to inspect the product. Installation constitutes product acceptance. Improper installation, application, use, care and maintenance voids warranty. Reference the TCNA Handbook and ANSI for installation guidance. Please visit bedrosians, com for current product information. We reserve the right to make product changes at any time without notice.