

12"x24" Field Tile - Matte



Alabaster  
100008054



Pewter  
100008055



Millstone  
100007651



Slate  
100007488

24"x48" Field Tile - Matte



Alabaster  
100007356



Pewter  
100007712



Millstone  
100007652



Slate  
100008056

24"x48" Paver - Matte



Alabaster  
100008057



Pewter  
100008058



Millstone  
100008059

1"x4" Straight Set Mosaic (12"x12" Sheet) - Matte



Alabaster  
100008060



Pewter  
100008061



Millstone  
100008062



Slate  
100008063



# Farmhouse Living

## Glazed Color Body Porcelain

Photo Features 24"x48" Field Tile - Matte in Pewter.


### SIZING & PACKAGING

Type	Shape	Alabaster Item Code	Millstone Item Code	Pewter Item Code	Slate Item Code	Size	Description	Pcs / Ctn	Sf / Ctn
Field		100008054	100007651	100008055	100007488	12"x24"	Field Tile - Matte	8	16.00
		100007356	100007652	100007712	100008056	24"x48"	Field Tile - Matte	2	16.00
		100008057	100008059	100008058		24"x48"	Paver - Matte	2	16.00
Trim		100008064	100008066	100008065	100008067	3"x24"	Bullnose - Matte	5	-
Mosaic		100008060	100008062	100008061	100008063	12"x12" Sheet	1"x4" Straight Set Mosaic - Matte	10	-

### ANSI TECHNICAL SPECIFICATIONS

	DCOF Acutest	PEI Rating ASTM# C1027	Frost Resistant ASTM# C1026	Scratch Resistance MOHS	Breaking Strength ASTM# C648	Water Absorption ASTM# C373	Chemical Resistance ASTM# C650
Results	≥ 0.42	N/A	Unaffected	7	≥ 300 lbf	≤ 0.5%	Unaffected

Shade Variation



### APPLICATIONS - NON-PAVERS

	Floors	Walls	Countertops	Shower Floors	Shower Walls	Pools/Spas
Residential	● †	■	■	● †	■	■
Commercial	● †	■	■	● †	■	■

### APPLICATIONS - PAVERS

	Floors	Walls	Countertops	Shower Floors	Shower Walls	Pools/Spas
Residential	■		■	■		■
Commercial	■		■	■		■

### LEGEND

- Product rated for Interior & Exterior use
- Product rated for Interior use only
- † May be suitable for Exterior Floors
- Ø Applications & ANSI Technical Specifications do not apply
- \* Special Order only

**IMPORTANT:** Installation Instructions - We recommend wet cutting or the score and snap method during the installation process. Improper installation techniques could expose installer to inhalation of harmful silica dust. Do not dry cut product using power tools during the installation process. Using dry cutting methods could present a risk of acute lung injury. If adequate ventilation cannot be achieved, wear a mask or respirator. For more information, see the SDS at [www.bedrosians.com/en/installation-care-maintenance/](http://www.bedrosians.com/en/installation-care-maintenance/).

† The TCNA does not rate products for exterior floors. Project specifier must determine product suitability for exterior floor applications by evaluating specific project conditions, type of use, traffic, drainage, expected contaminants (such as water, oil, grease, etc.), wear, maintenance, and manufacturer's specifications and guidelines. Use caution--product may not be suitable for pool decks. Not suitable for ramps. No polished tiles; only textured surfaces may be suitable.

Merchandising materials and samples are for general reference only and representative of a product's potential characteristics. Tile is subject to variation in color/shade, size, texture, and finish. Field, mosaic and trim tile may not match exactly. Blend tiles from different boxes to achieve consistent shade distribution. Installer and end user must conduct a dry mock layout under proper lighting conditions to inspect the product. Installation constitutes acceptance of the product. Reference the TCNA, ANSI, Manufacturer's specifications, and Bedrosians Care & Maintenance Guide. Improper installation, application, use, care and maintenance voids warranty. We reserve the right to make product changes without notice. Please visit [bedrosians.com](http://bedrosians.com) for current product information.

