

Rectified Field Tile Sizes



Grey - GR
CRDOTHGR848-N - 8"x48" Rectified Field Tile - Honed



Dark Grey - DG
CRDOTHDG848-N - 8"x48" Rectified Field Tile - Honed



Oak - OA
CRDOTHOA848-N - 8"x48" Rectified Field Tile - Honed



Clay - CL
CRDOTHCL848-N - 8"x48" Rectified Field Tile - Honed



Cinnamon - CI
CRDOTHCI848-N - 8"x48" Rectified Field Tile - Honed



Brown - BR
CRDOTHBR848-N - 8"x48" Rectified Field Tile - Honed



Othello

Glazed Color Body Porcelain

Photo Features 8"x48" Rectified Field Tile - Honed in Brown.


SIZING & PACKAGING

| Type | Shape | Item Code | Size | Description | Pcs / Ctn | Sf / Ctn |
|-------|-------|--------------|--------|------------------------------|-----------|----------|
| Field | | CRDOTH•848-N | 8"x48" | Rectified Field Tile - Honed | 4 | 10.33 |

ANSI TECHNICAL SPECIFICATIONS


| | DCOF Acutest | PEI Rating ASTM# C1027 | Frost Resistant ASTM# C1026 | Scratch Resistance MOHS | Breaking Strength ASTM# C648 | Water Absorption ASTM# C373 | Chemical Resistance ASTM# C650 |
|---------|--------------|------------------------|-----------------------------|-------------------------|------------------------------|-----------------------------|--------------------------------|
| Results | ≥ 0.42 | Pass ≤ 175 (ISO) | Unaffected | N/A | Pass (1,300 ISO) | ≤ 0.5% | Unaffected |

Shade Variation




APPLICATIONS

| | Floors | Walls | Countertops | Shower Floors | Shower Walls | Pools/Spas |
|-------------|--------|-------|-------------|---------------|--------------|------------|
| Residential | ● † | ☐ | ☐ | ● † | ☐ | ☐ |
| Commercial | ● † | ☐ | ☐ | ● † | ☐ | ☐ |



LEGEND

- ☐ Product rated for Interior & Exterior use
- Product rated for Interior use only
- † May be suitable for Exterior Floors
- ⊘ Applications & ANSI Technical Specifications do not apply
- * Special Order only



Use of a leveling system during installation is strongly recommended

† The TCNA does not rate products for exterior floors. Project specifier must determine product suitability for exterior floor applications by evaluating specific project conditions, type of use, traffic, drainage, expected contaminants (such as water, oil, grease, etc.), wear, maintenance, and manufacturer's specifications and guidelines. Use caution--product may not be suitable for pool decks. Not suitable for ramps. No polished tiles; only textured surfaces may be suitable.

Merchandising materials and samples are for general reference only and representative of a product's potential characteristics. Tile is subject to variation in color/shade, size, texture, and finish. Field, mosaic and trim tile may not match exactly. Blend tiles from different boxes to achieve consistent shade distribution. Installer and end user must conduct a dry mock layout under proper lighting conditions to inspect the product. Installation constitutes product acceptance. Improper installation, application, use, care and maintenance voids warranty. Reference the TCNA Handbook and ANSI for installation guidance. Please visit bedrosians.com for current product information. We reserve the right to make product changes at any time without notice.

