Bedrosians[®] Tile & Stone

FrammentaGlazed Color Body Porcelain

Field Tile Sizes



White - WHI FIOFRAWHI2424 24"x24" Rectified Field Tile - Matte



Beige - BEI FIOFRABEI2424 24"x24" Rectified Field Tile - Matte



Light Grey - LIG FIOFRALIG2424 24"x24" Rectified Field Tile - Matte



Dark Grey - DAR FIOFRADAR2424 24"x24" Rectified Field Tile - Matte

Palladiana Mosaic - Matte (12"x12" Sheet)



White - WHI FIOFRAWHIPALMO



Beige - BEI FIOFRABEIPALMO



Light Grey - LIG



Dark Grey - DAR FIOFRADARPALMO





SIZING & PACKAGING

| Type | Shape | Item Code | Size | Description | Pcs / Ctn | Sf / Ctn |
|--------|-------|----------------|---------------|------------------------------|-----------|----------|
| Field | | FIOFRA•••2424 | 24"x24" | Rectified Field Tile - Matte | 4 | 15.72 |
| Trim | | FIOFRA···324BN | 3"x24" | Bullnose - Matte | 10 | - |
| Mosaic | | FIOFRAPALMO | 12"x12" Sheet | Palladiana Mosaic - Matte | 11 | 10.66 |

ANSI TECHNICAL SPECIFICATIONS


| | DCOF Acutest | PEI Rating ASTM# C1027 | Frost Resistant ASTM# C1026 | Scratch Resistance MOHS | Breaking Strength ASTM# C648 | Water Absorption ASTM# C373 | Chemical Resistance ASTM# C650 |
|--------------|-----------------|------------------------------|-----------------------------------|-------------------------------|------------------------------------|-----------------------------------|--------------------------------------|
| Results | ≥0.42 | 4 | N/A | N/A | N/A | ≤0.5% | Unaffected |
| APPLICATIONS | | | | | | | |
| | | Floors | Walls | Countertops | Shower Floors | Shower Walls | Pools/Spas |
| Residential | | •† | • | • | • † | • | • |
| Commercial | | • † | • | 0 | •† | • | • |

LEGEND


- Product rated for Interior & Exterior use
 - Applications & ANSI Technical Specifications do not apply
- Product rated for Interior use only
 - * Special Order only
- † May be suitable for Exterior Floors








V3-Moderate





Use of a leveling system during installation is strongly recommended

Merchandising materials and samples are for general reference only and representative of a product's potential characteristics. Tile is subject to variation in color/shade, size, texture, and finish. Field, mosaic and trim tile may not match exactly. Blend tiles from different boxes to achieve consistent shade distribution. Installer and end user must conduct a dry mock layout under proper lighting conditions to inspect the product. Installation constitutes product acceptance. Improper installation, application, use, care and maintenance voids warranty. Reference the TCNA Handbook and ANSI for installation guidance. Please visit bedrosians.com for current product information. We reserve the right to make product changes at any time without notice.



The TCNA does not rate products for exterior floors. Project specifier must determine product suitability for exterior floor applications by evaluating specific project conditions, type of use, traffic, drainage, expected contaminants (such as water, oil, grease, etc.), wear, maintenance, and manufacturer's specifications and guidelines. Use caution--product may not be suitable for pool decks. Not suitable for ramps. No polished tiles; only textured surfaces may be suitable.