# Bedrosians<sup>®</sup> Tile & Stone

#### Field Tile Sizes



Bianco - BIA INCROMBIA1224 12"x24" Non-rectified Field Tile - Matte



Latte - LAT INCROMLAT1224 12"x24" Non-rectified Field Tile - Matte



Clay - CLA INCROMCLA1224 12"x24" Non-rectified Field Tile - Matte



Spice - SPI INCROMSPI1224 12"x24" Non-rectified Field Tile - Matte



Bianco - BIA INCROMBIA2121 21"x21" Non-rectified Field Tile - Matte



Latte - LAT INCROMLAT2121 21"x21" Non-rectified Field Tile - Matte



Clay - CLA INCROMCLA2121 21"x21" Non-rectified Field Tile - Matte



Spice - SPI INCROMSPI2121 21"x21" Non-rectified Field Tile - Matte

### 2"x2" Mosaic - Matte (13"x13" Sheet)



Bianco - BIA INCROMBIA22MO



Latte - LAT INCROMLAT22MO



Clay - CLA INCROMCLA22MO



Spice - SPI INCROMSPI22MO



#### SIZING & PACKAGING

Type	Shape	Item Code	Size	Description	Pcs / Ctn	Sf / Ctn
Field		INCROM····1224	12"x24"	Non-rectified Field Tile - Matte	10	20.35
		INCROM***2121	21"x21"	Non-rectified Field Tile - Matte	7	22.30
Trim		INCROM•••324BN	3"x12"	Surface Bullnose - Matte	24	-
Mosaic		INCROM•••22MO	13"x13" Sheet	2"x2" Mosaic - Matte	11	-

#### ANSITECHNICAL SPECIFICATIONS

	DCOF Acutest	PEI Rating ASTM# C1027	Frost Resistant ASTM# C1026	Scratch Resistance MOHS	Breaking Strength ASTM# C648	Water Absorption ASTM# C373	Chemical Resistance ASTM# C650
Results	≥0.42	4	Unaffected	7	≥550 lbf	≤0.5%	Unaffected

#### **APPLICATIONS**

	Floors	Walls	Countertops	Shower Floors	Shower Walls	Pools/Spas
Residential	•	•	•	•	•	•
Commercial	•	•	•	•	•	•

## LEGEND

Product rated for Interior & Exterior use

 $\varnothing$  Applications & ANSI Technical Specifications do not apply

- Product rated for Interior use only
  - \* Special Order only
- † May be suitable for Exterior Floors




33% Overlap should not exceed 33%

Shade Variation

V3-Moderate

Minimum 3/16" Grout Joint













Merchandising materials and samples are for general reference only and representative of a product's potential characteristics. Tile is subject to variation in color/shade, size, texture, and finish. Field, mosaic and trim tile may not match exactly. Blend tiles from different boxes to achieve consistent shade distribution. Installer and end user must conduct a dry mock layout under proper lighting conditions to inspect the product. Installation constitutes product acceptance. Improper installation, application, use, care and maintenance voids warranty. Reference the TCNA Handbook and ANSI for installation guidance. Please visit bedrosians.com for current product information. We reserve the right to make product changes at any time without notice.

