

Field Tile Sizes



Michelangelo - MIC
STPZEBMIC1224 - 12"x24" Rectified Field Tile - Matte



Calacatta - CAL
STPZEBCAL1224 - 12"x24" Rectified Field Tile - Matte



Classico - CLA
STPZEBCLA1224 - 12"x24" Rectified Field Tile - Matte



Bluette - BLU
STPZEBBLU1224 - 12"x24" Rectified Field Tile - Matte

Mosaics Available



Michelangelo - MIC
STPZEBMIC22MO
2"x2" Mosaic - Matte
(12"x12" Sheet)



Calacatta - CAL
STPZEBCAL22MO
2"x2" Mosaic - Matte
(12"x12" Sheet)



Classico - CLA
STPZEBCLA22MO
2"x2" Mosaic - Matte
(12"x12" Sheet)



Bluette - BLU
STPZEBBLU22MO
2"x2" Mosaic - Matte
(12"x12" Sheet)



Michelangelo - MIC
STPZEBMICCHEMO
Chelsea Mosaic - Matte
(9"x15" Sheet)



Calacatta - CAL
STPZEBCALCHEMO
Chelsea Mosaic - Matte
(9"x15" Sheet)



Classico - CLA
STPZEBCLACHEMO
Chelsea Mosaic - Matte
(9"x15" Sheet)



Bluette - BLU
STPZEBBLUCHEMO
Chelsea Mosaic - Matte
(9"x15" Sheet)



Zebrino

Glazed Color Body Porcelain


Photo Features 9"x15" Chelsea Mosaic Tile - Matte in Bluette.

SIZING & PACKAGING

Type	Shape	Item Code	Size	Description	Pcs / Ctn	Sf / Ctn
Field		STPZEB***1224	12"x24"	Rectified Field Tile - Matte	8	15.75
Trim		STPZEB***424BN	4"x24"	Bullnose - Matte	16	1.30
Mosaic		Ø STPZEB***22MO	12"x12" Sheet	2"x2" Mosaic - Matte	5	3.48
		Ø STPZEB***CHEMO	9"x15" Sheet	Chelsea Mosaic - Matte	5	3.53


ANSI TECHNICAL SPECIFICATIONS

	DCOF Acutest	PEI Rating ASTM# C1027	Frost Resistant ASTM# C1026	Scratch Resistance MOHS	Breaking Strength ASTM# C648	Water Absorption ASTM# C373	Chemical Resistance ASTM# C650
Results	≥ 0.42	N/A	Unaffected	7	≥ 350 lbf	≤ 0.5%	Unaffected



APPLICATIONS


	Floors	Walls	Countertops	Shower Floors	Shower Walls	Pools/Spas
Residential	●†	■	■	●†	■	■
Commercial	●†	■	■	●†	■	■



LEGEND

- Product rated for Interior & Exterior use
- Product rated for Interior use only
- † May be suitable for Exterior Floors
- Ø Applications & ANSI Technical Specifications do not apply
- * Special Order only

PRODUCT CERTIFIED FOR LOW CHEMICAL EMISSIONS: UL COMF/G3 UL 2818



† The TCNA does not rate products for exterior floors. Project specifier must determine product suitability for exterior floor applications by evaluating specific project conditions, type of use, traffic, drainage, expected contaminants (such as water, oil, grease, etc.), wear, maintenance, and manufacturer's specifications and guidelines. Use caution--product may not be suitable for pool decks. Not suitable for ramps. No polished tiles; only textured surfaces may be suitable.

Merchandising materials and samples are for general reference only and representative of a product's potential characteristics. Tile is subject to variation in color/shade, size, texture, and finish. Field, mosaic and trim tile may not match exactly. Blend tiles from different boxes to achieve consistent shade distribution. Installer and end user must conduct a dry mock layout under proper lighting conditions to inspect the product. Installation constitutes product acceptance. Improper installation, application, use, care and maintenance voids warranty. Reference the TCNA Handbook and ANSI for installation guidance. Please visit bedrosians.com for current product information. We reserve the right to make product changes at any time without notice.

